



LABELLING SYSTEMS

PLX Range
Data Sheet










Applicators and Print & Apply Labelling Machines

Xact specialise in the supply of labelling machines for industry. Whether you need an off the shelf Label Applicator or a bespoke solution, Xact will help you find the right solution. Supported across the UK and Ireland by our team of dedicated technical sales and engineering personnel, their expertise ensures the highest levels of service starting with the initial specification process through to installation and ongoing support.

Industries

- Construction
- Food & beverage
- Pharmaceuticals
- Packaging
- Industrial
- Chemical
- Automotive



Why choose Xact?

- Over 40 years experience in product labelling & coding
- Manufactured in the UK
- Applicator and print & apply solutions
- Designed for 24/7 operation
- User friendly touchscreen controls
- Customised & fully integrated solutions
- Options for integrated thermal and inkjet printing systems

Xact, 20-24 Gibraltar Row, King Edward Industrial Estate, Liverpool, L3 7HJ

E: info@xactpack.co.uk | **T:** 0151 479 3020 | **W:** xactpack.co.uk

©2016 Xact



PLX LABELLING RANGE

Technical Specification

APPLICATOR	PLX JUNIOR	PLX01	PLX02	PLX03
Min/max label width (inc liner)	10mm – 100mm	10mm – 75mm	10mm – 155mm	10mm – 215mm
Min/max label length	20mm – 150mm	10mm – 600mm	10-600mm	10mm-600mm
Max. dispensing speed (m/min)	60mpm	90mpm	90mpm	90mpm
Reel holder	250mm reel holding disk	300mm reel holding disk	300mm reel holding disk	300mm reel holding disk
Motor drive	Servo drive motor 200w	Servo drive motor 400w	Servo drive motor 400w	Servo drive motor 400w
Rewind	Internal rewind only	External rewinder (internal option)	External rewinder (internal option)	External rewinder (internal option)
Display/controls	HMI	HMI	HMI	HMI
Label sensor	Infrared/Ultrasonic	Infrared/Ultrasonic	Infrared/Ultrasonic	Infrared/Ultrasonic

APPLICATOR	PLX 04	PLX05	Customised Solutions
Min/max label width (inc liner)	10mm – 250mm	10mm – 305mm	Specify
Min/max label length	10mm – 600mm	10mm – 600mm	Specify
Max. dispensing speed (m/min)	90mpm	90mpm	Specify
Reel holder	300mm reel holding disk	300mm reel holding disk	Specify
Motor drive	Servo drive motor 200w	Servo drive motor 400w	Specify
Rewind	Internal rewind only	External rewinder (internal option)	Specify
Display/controls	HMI	HMI	Specify
Label sensor	Infrared/Ultrasonic	Infrared/Ultrasonic	Specify

*The above have the facility to be customised.

STAND OPTIONS

- Side stand (castors or levelling feet)
- Overhead stand (castors or levelling feet)
- Customised mounting assemblies

PRINTING OPTIONS

- Thermal print engine (various options available)
- Inkjet printing
- Hot foil coder
- Thermal coder